



# Handling and maintenance

## of the BCD 360 Knot Filler applicator

### Technical Info

- Applicator for 12 mm sticks.
- Robust and reliable tool.
- 300 watts for greater adhesive output.
- External temperature control from 140 °C to 230 °C.
- Light-weight model.
- Non breakable circular TPR handle for comfortable long hour operation.
- Unique effort-saving trigger.



The tool must be placed on the metal stand.



Never place the heated tool on its side.



Never point the nozzle upwards.

### ► Handling

Please note the following handling points

- ✓ Let the gun heat for 3-4 minutes!
- ✓ Never pull a stick backwards from the gun.
- ✓ Recommended temperature setting 160 °C.
- ✓ Tighten the nozzle regularly.
- ✓ Use only recommended adhesives.
- ✓ Keep the melting chamber free of dirt and dust.
- ✓ Protect the device from moisture and liquids.



External temperature control



Flow adjustment



Ergonomical trigger

### ► Claims

Important info regarding claims

When we dismantle a tool, we can always see what caused the malfunction. In 99% of the cases, one of the below mentioned points has occurred - they are not valid reasons for a complaint. If you are convinced that none of the points have occurred, we will gladly check the tool in our workshop.

*The following errors are not valid reasons for a complaint:*

- The gun was placed on its side.
- The nozzle was held upwards for too long.
- The tool was not heated enough before starting.
- A stick was pulled backwards from the gun.
- The temperature was set too high.